



HEAVY DUTY RECTANGULAR RECEIVING CONTAINERS

Specifications for Heavy Duty containers:

FLOORS:

- 1/4" floor sheets (2 pieces)
- 12" centered crossmembers (3" x 4.1# channel)
- 6" x 2" x 1/4" tube main rails
- 8" x 10" rear ground rollers with zerk
- 8" x 6" front ground rollers with zerk (cable hook only)

SIDES:

- 7 ga. sheets with FORMED BOTTOM
- 12 ga. post (4 way bent) on 12" centers on the rear 8ft. & 24" centers on the remainder
- 3/16" rear post w/ 6" x 3" ratchet receiving opening w/ 1/2" reinforcing plate
- 4" x 3" x 3/16" tube top rail
- 2" fire port on each side
- Uplift latch system

FRONT ENDS:

- 7 ga. Sheet w/ 4" x 3" x 3/16" tube top rail & 12 ga. front post
- 3/16" Push plate and Full dog box

TAILGATES:

- 7ga. tailgate w/ 4" x 3" x 3/16" tube vertical & horizontal supports, (Openings per customer spec.)
- 5/8" hinge plate with 1 1/4" hinge pins (3 hinges on 61" and taller containers)

ROOFS:

- 7ga. sheets & 10 ga. Post aligned with side post

PAINT: water based industrial enamel

All containers are painted gray on the bottom and the interior.
The exterior of all containers are painted one (1) standard TFI color of choice

THOMPSON FABRICATING, INC.

60 Council Ave., P.O. Box 432 • Wheatland, PA 16161
Toll free: 888.318.8876 • Tel: 724.981.8876 • Fax: 724.981.8664
sales@thompsonfab.com
www.thompsonfab.com