



STANDARD DUTY

RECTANGULAR HOOK LIFT CONTAINERS

Standard duty containers are designed and built for the construction and demolition industries.

These containers can be used on both Residential and Commercial job sites to haul a wide array of material ranging from yard waste and roofing materials to light scrap iron and concrete.

Standard Duty containers can easily withstand the abuse and loading procedures that you typically see on the construction site such as excavators, backhoes, skid loaders and grapples.

Specifications for Standard Duty containers:

FLOORS:

- 3/16" floor sheets (2 pieces)
- 16" centered crossmembers (3" x 4.1# channel)
- 6" x 2" x 1/4" tube main rails
- 8" x 10" rear ground rollers with zerk
- Rear hold downs per customer spec.

SIDES:

- 10 ga. sheets with ROLLED BOTTOM
- 12 ga. post on 24" centers (4-way bent)
- 3/16" rear post
- 4" x 3" x 3/16" tube top rail
- 5/8" solid round bar tarp rail (30" down)
- Uplift latch system

FRONT ENDS:

- 10 ga. sheet w/ 4" x 3" x 3/16" tube top rail & 12 ga. front post
- 6" x 2" x 1/4" A-frame with 5/8" flame cut pin brackets
- 36" hook height 1 1/2" solid Round Bar
- 54" hook height 2" or 2 1/2" solid Round Bar
- 62" hook height 2 1/2" solid Round Bar

TAILGATES:

- 10 ga. Sheet w/ 4" x 3" x 3/16" tube vertical supports, and 10 ga. 4-way bent cross post
- 5/8" hinge plate with 1 1/4" hinge pins (3 hinges on 61" and taller containers)

PAINT: water based industrial enamel

All containers are painted gray on the bottom and the interior.

The exterior of all containers are painted one (1) standard TFI color of choice

THOMPSON FABRICATING, INC.

60 Council Ave., P.O. Box 432 • Wheatland, PA 16161

Toll free: 888.318.8876 • Tel: 724.981.8876 • Fax: 724.981.8664

sales@thompsonfab.com

www.thompsonfab.com